US009637012B2

(12) **United States Patent**
Biagini

(10) **Patent No.: US 9,637,012 B2**
(45) **Date of Patent: May 2, 2017**

(54) **CHARGING DEVICE HAVING ADAPTIVE INPUT**

(71) Applicant: **INTELLIGENT ELECTRONIC SYSTEMS**, Saint-Aunes (FR)

(72) Inventor: **Eric Biagini**, Perols (FR)

(73) Assignee: **INTELLIGENT ELECTRONIC SYSTEMS**, Montpellier (FR)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 128 days.

(21) Appl. No.: **14/400,102**

(22) PCT Filed: **Jun. 7, 2013**

(86) PCT No.: **PCT/FR2013/051312**
§ 371 (c)(1),
(2) Date: **Nov. 10, 2014**

(87) PCT Pub. No.: **WO2013/182825**
PCT Pub. Date: **Dec. 12, 2013**

(65) **Prior Publication Data**

US 2015/0115888 A1 Apr. 30, 2015

(30) **Foreign Application Priority Data**

Jun. 7, 2012 (FR) 12 01646

(51) **Int. Cl.**
H02J 7/00 (2006.01)
B60L 11/18 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC ***B60L 11/1811*** (2013.01); ***B60L 11/1812*** (2013.01); ***B60L 11/1838*** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC B60L 11/1811; B60L 11/1812; B60L 11/1838; H02J 7/02; H02J 7/04; H02J 7/0055
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

2004/0217746 A1* 11/2004 Thiery H02M 1/425 323/282
2007/0159141 A1* 7/2007 Shih G05F 1/70 323/207
(Continued)

FOREIGN PATENT DOCUMENTS

CN 201594757 9/2010
CN 202142879 2/2012

OTHER PUBLICATIONS

Su et al: "Current source inverter based traction drive for EV battery charging applications", 2011 IEEE Vehicle Power and Propulsion Conference, 12339364, 2011, pp. 1-6, XP002692761, Pistacaway, NJ, USA DOI: 10.1109/vppc.2011.6043143 ISBN: 978-1-61284-248-6.

Primary Examiner — Paul Dinh
(74) *Attorney, Agent, or Firm* — Duane Morris LLP; J. Rodman Steele, Jr.; Gregory M. Lefkowitz

(57) **ABSTRACT**

The invention relates to a charging device (**2**) for a battery (**5**) of a motorized device, suitable for being supplied by a single-phase alternating input current, and suitable for being supplied by a multi-phase alternating input current, said charging device (**2**) including a first conversion module (**3**) and a second conversion module (**4**), the first conversion module (**3**) being suitable for converting an alternating current into at least one intermediate direct current and of supplying the second conversion module (**4**) with said intermediate current, and the second conversion module (**4**) being suitable for converting the intermediate current into a
(Continued)